

## CEROIL COOLANT – ANTIFREEZE 30%

Direct Use. Protection -18°C

Version 1 Date of issue: 01/03/2023

Page 1 de 2  
Date of printing: 19/05/2023

### PRODUCT

New generation coolant-antifreeze made with 30% glycols, with corrosion inhibitors and distilled-demineralized water. For all types of vehicles. Direct use.

**PROPERTIES** Does not contain amines, nitrites, phosphates, nitrates and silicates. Prevents the formation of decompositions harmful to vehicles and people. Excellent thermal conductivity. It begins to crystallize in the laboratory at -14.5°C. Antifreeze for all kinds of vehicles and refrigeration systems. It protects or covers all the components that make up radiators, water pumps and cooling circuits and is considered "MULTIMETAL", not attacking rubbers, copper, brass, welding aluminum and its mixtures, etc.

It meets all the specifications required worldwide for this type of products and therefore its use is guaranteed for any vehicle, machinery, etc. It does not produce foaming

Disponible en 1L y 5L



# CEROIL COOLANT – ANTIFREEZE 30%

Direct Use. Protection -18°C

Version % Date of issue. \$%#\$' #&\$&'

Date & Xe &  
Date of printing. %- #)\$) #&\$&'

## TECHNICAL DATA

ANTIFREEZE! COOLANT <b>C.C.</b> <b>30%</b>	Method	Value
Aspect	Visual	Liquid
Colour	Visual	; green/Pink
Density a 20°C, kg/l	ASTM D-4052	1.040-1.050
Refraction Index, °C	ASTM D-1218	1.360-1.370
Alkaline reserve, ml HCl 0.1N	ASTM D-1121	0.6-2.6
Freezing Point, °C	ASTM D-1177	-18°C+/-1%
pH	ASTM D-1287	7.5-9.0
Boiling Point, °C	ASTM D-1120	120°C+/-1%

## Quality Levels/ Specifications

UNE 26.361.88

ASTM D-3306

SAE J-1034



**Respetuosos con el  
MEDIOAMBIENTE**