

# CEROIL COOLANT – ANTIFREEZE 50%

Direct Use. Protection -35°C

Versión 1 Date of issue: 01/03/2023

Page 1 de 2  
Date of printing: 18/05/2023

## PRODUCT

New generation coolant-antifreeze made with 50% glycols, with corrosion inhibitors of organic technology and distilled-demineralized water. For all types of vehicles. Direct use.

## PROPERTIES

Does not contain amines, nitrites, phosphates, nitrates and silicates. Silicate free. Prevents the formation of decompositions harmful to vehicles and people. Excellent thermal conductivity. It begins to crystallize in the laboratory at -32°C. It protects or covers all the components that make up radiators, water pumps and cooling circuits and is considered "MULTIMETAL", not attacking rubbers, copper, brass, welding aluminum and its mixtures, etc. It meets all the specifications required worldwide for this type of products and therefore its use is guaranteed for any vehicle, machinery, etc.

It does not produce foaming

## TECHNICAL DATA

CEROIL COOLANT - ANTIFREEZE C.C. 50%	Method	Value
Aspect	Visual	Liquid
Colour	Visual	; reen/Pink
Density a 20°C, kg/l	ASTM D-4052	1.060-1.075
Refractive Index, °C	ASTM D-1218	1.380-1.390
Alkaline Reserve, ml HCl 0.1N	ASTM D-1121	1.0-3.5
Freezing point, °C	ASTM D-1177	-35°C+/-1%
pH	ASTM D-1287	7.5-9.0
Boiling Point, °C	ASTM D-1120	108°C+/-1%

# CEROIL COOLANT – ANTIFREEZE 50%

Direct Use. Protection -35°C

Versión 1 Date of issue: **01/03/2023**

Page 2 de 2  
Date of printing: **18/05/2023**

E u]tm`ej e`g

- UNE 26.361.88
- ASTM D-3306
- ASTM D-4656
- ASTM D-4985
- SAE J-1034
- BS 6580
- AFNOR NFR 15-601
- IVECO
- MAN
- SCANIA
- VOLVO



Aj U]UWe en 1L. y 5 L.



**Respetuosos con el  
MEDIOAMBIENTE**